



FO Patch Panel ST Type 24 Port

SL05SPP24PR01



Dimension(L×W×H):480mm×220mm×1Umm

Features:

1. The shell is high intensified & insulated material, thus having excellent mechanic performance and
2. it is solid and durable
3. fiber in put:4
4. Adapters output:24
5. strength core and shell was Insulation,add with grounding lead
6. Can be installed against wall
7. Full accessories for convenient operations

Performance

excellent design

maximum cores 24

fiber lead 、 grounding and perfect fixup 、 reliable

pigtail fixup reliable and perfect protection

Apply to extensive field

convenient operations and maintenance

Specifications:

Environment temperature: $-25^{\circ}\text{C} \sim +45^{\circ}\text{C}$

Relative humidity: $\leq 85\%$ (30°C 时)

Atmosphere pressure: $70 \sim 106\text{KPa}$

Insulated Resistance: $\geq 2 \times 10\text{M}\Omega/500\text{V}$ (DC)

Intensity $\leq 15\text{KV}(\text{DC})/1\text{min}$ no spark-over and no flying arc

Fiber bending radium guaranteed more than 40mm: $\geq 40\text{mm}$

Application: It is applicable for straight-through connection and diverged connection in aerial layout , duct and direct buried. It can protect fiber connectors.