


SL5CB2411

Color cord

1. Blue-White/Blue
2. Orange-White/Orange
3. Green-White/Green
4. Brown-White/Brown

ITEM		
No. of Cord. (芯線數)		4 Pair 對
Conductor 導體	Material (材質)	Bare Copper Solid (裸銅線)
	Construction (結構)	24AWG; 1/0.51 ± 0.008 mm
Insulation 絕緣	Material (材質)	Polyethylene
	Thickness (厚度)	0.20±0.02 mm
	Diameter (外徑)	0.92 ± 0.05 mm
Inner Layer 內絞合	Direction (絞向)	S(右向)
	Pitch (絞距) REF	30mm underneath
Outside Layer 外絞合	Direction (絞向)	S(右向)
	Pitch (絞距) REF	100±10mm
Rip cord 撕裂線	Material (材質)	Nylon
Jacket 被覆	Material (材質)	flame retardant PVC
	Thickness (厚度)	0.50 mm(Min. Thickness: 0.40mm)
	Diameter (外徑)	5.2 ± 0.20 mm
	Color (顏色)	Optional
Marking	Optional	

頻率f (MHZ)	Zin-0S (ohm)	Fitted Z (Ohm)	SRL (dB)	ATT (PATCH) (dB/100M)	DELAY (ns/100M)	MAX. DELAY SKEW(ns/100M)	NEXT (dB)	PSNEXT (dB)
0.772	100±15	100±15	19.40	1.8	574.97	45.0	67	64
1			20.00	2	570	45.0	65.3	62.31
4			23.00	4.1	552.00	45.0	56.3	53.28
8			24.50	5.8	546.73	45.0	51.8	48.77
10			25.00	6.5	545.38	45.0	50.3	47.31
16			25.00	8.2	543.00	45.0	47.3	44.25
20			25.00	9.3	542.05	45.0	45.8	42.8
25			24.30	10.4	541.20	45.0	44.3	41.35
31.25			23.60	11.7	540.44	45.0	42.9	39.89
62.5			21.50	17	538.55	45.0	38.4	35.38
100			20.10	22	537.60	45.0	35.3	32.31

DRWN.	ChenFeng	SPEC NO:	Construction: 24AWG x 4P
CHKD.	Gao	SL5CB2411	Customer:
APPD.	Gao	DATE:6-30-2007	

SUR-LINK TECHNOLOGY CO.,LTD.
ELECTRICAL PROPERTIES(電氣特性)

ITEM	
Conductor Resistance (導體電阻)	Max. 93.8 ohms/km at 20°C
Insulation Resistance (絕緣電阻)	Min. 5000 mega ohms-km at 20°C
Dielectric Test (耐電壓)	1000V DC /1 min ; No Breakdown
Impedance (特性阻抗)	100 ohms ± 15%
Temperature Rating (額定溫度)	75°C
Voltage Rating (額定電壓)	30V