

SL3KJUT011103

NOTES:

ELECTRICAL:

- 1.VOLTAGE RATING : 125 VAC RMS
- 2.CURRENT RATING : 1.5 AMP
- 3.CONTACT RESISTANCE :100 MILLIOHMS MAX
- 4.INSULATION RESISTANCE :1000 MEGOHMS MIN @ 500 VDC
- 5.DIELECTRIC STRENGTH :750 VAC RMS 60Hz,1MIN

ENVIRONMENTAL:

- 1.STORAGE : -40° TO +85°
- 2.OPERATION : 0° TO 70°
- CONFORM TO ANSI/TIA/EIA 568B CATEGORY 3
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68,SUBPART F.

MECHANICAL:

- 1. HOUSING MATERIAL :PC UL94V-0
- 2. INSERT MATERIAL :FLAME RETARDANCY ABS UL94V-0
- 3. PCB MATERIAL :FR-4 THICKNESS:1.6mm
- 4. CONTACT MATERIAL :PHOSPHOR BRONZE STAMP PIN T=0.35mm
- 5. IDC CONTACT MATERIAL :PHOSPHOR BRONZE T=0.50mm WITH NICKEL PLATING
- 6. WIRE :AWG 24~26

PART NUMBER:SL3KJUT011103

